



# FORMEUSE DE BOÎTES

## ETL F60 - ETL F60II

- Machine simple ou double tête de mise en volume par verrouillage.
- Châssis inox
- Magasin de stockage des découpes à plat d'une autonomie de 10 mn.
- Contrôle par cellule du niveau de découpes dans le magasin.
- Contrôle par cellule du niveau d'accumulation des boîtes formées sur le convoyeur lanceur, permettant la gestion de la prise des découpes (en option).
- Armoire électrique inox intégrée
- Contrôle / Commande par automate programmable.

• **Alimentation électrique :**

- 2,5 kW – 400 V (3ph + N)- 50 Hz  
(autre alimentation sur demande)

• **Alimentation pneumatique :** 6 bars.

• **Dimensions F60 :** 1560 x 1650 x 2400 mm

• **Dimensions F60II :** 1800 x 1650 x 2210 mm

• **Poids :** 450 Kg et 680 Kg

• **Machine multi-format :**

- Par changement d'outillage (magasin, poinçon, matrice) en verrouillage.


• **Cadence :**

F60 : de 5 à 60 boîtes/mn en verrouillage

F60II : de 5 à 120 boîtes/mn en collage

• **Formats standards de boîte :**

- Longueur : 90 - 480 mm
- Largeur : 65 - 210 mm
- Hauteur : 25 - 90 mm



Emballage  
Technologies

Z.A. de Troyalac'h - CP 19 - 29563 QUIMPER cedex 9 - FRANCE  
Tél. +33 (0)2 98 94 69 99 - Fax : +33 (0)2 98 94 67 59  
[www.emballage-technologies.com](http://www.emballage-technologies.com)



# FORMING MACHINES

## ETL F60 - ETL F60II

- Compact mechanical forming machine for carton/thin corrugated board
- Stainless steel frame
- Carton magazine. Time between feeding approximately 10 mn
- Low level carton magazine cell
- Queue control cell on outfeed conveyor (in option)
- Integrated electrical cabinet

### Power supply :

- 2,5 kW (5 kW by gluing) – 400 V (3ph + N)- 50 Hz
- (other supply voltage on request)

### Air supply : 6 bars.

**Dimensions F60 :** 1560 x 1650 x 2400 mm

**Dimensions F60II :** 1800 x 1650 x 2210 mm

**Weight :** 450 Kg and 680 Kg

### Multisize machine :

- By change of the tooling and blank magazines

### Production rate :

F60 : Up to 60 carton per minute by mechanical latching

F60II : Up to 120 carton per minute by mechanical latching

### Box dimensions :

- Length : 90 - 480 mm
- Width : 65 - 210 mm
- Height : 25 - 90 mm

